



PHILIPS



Consumer Lighting
India Trade Catalogue

2019

1st March, 2019



INDOOR



Smartbrite Extra Batten

Wattage available: 22W

Model Number:

BN 021 LED25S 6500 PSU GR S1

BN 021 LED25S 4000 PSU GR S1

Specifications & Features

- Higher Lumen (2500lm output), more energy saving (110lm/W, 22W)
- Extruded aluminum housing (enhances safety) with high quality polycarbonate diffuser
- Long life: 25,000 burning hours
- Wide voltage protection range 140V-270V
- Available in NW (4000K) & CDL (6500K)

MRP: 22W: ₹ 950/-

HSN Code: 94051090



Smartbrite Batten

Wattage available: 10W & 21W

Model Number:

BN 021C LED20S PSU CDL/NW GR

BN 021 LED10S- 6500/4000 PSU GR S1

Specifications & Features

- Extruded aluminum housing (enhances safety) with high quality polycarbonate diffuser
- Available in 2ft: 10W/1150lm & 4ft: 21W/2000lm
- Long life: 25,000 burning hours
- Wide voltage protection range 140V-270V
- Available in NW (4000K) & CDL (6500K)

MRP: 10W: ₹ 570/-, 21W: ₹ 850/-

HSN Code: 94051090



Smartbright Waterproof

Dust and waterproof luminaire

Wattage available: 20W & 40W

Model Number:

WT200C LED40S 6500 PSU L120/4000
PSU L120

WT200C LED20S-6500/4000 PSU L60

Specifications & Features

- IP65, Dust and waterproof Led luminaire with polycarbonate housing and SS hardware
- Available in 2ft: 2000lm/20W & 4ft: 4000lm/40W
- Long life: 25,000 burning hours
- Suitable for both wall and suspended mounting with relevant mounting accessories

MRP: 20W: ₹ 2,600/-
40W: ₹ 3,800/-

HSN Code: 94051090



Vista Glow

Wattage available: 6.5W

Model Number:

WT140W LED7S CW PSU S1 PC

WT140W LED7S NW PSU S1 PC

Specifications & Features

- Pressure die cast housing
- Long life: 25,000 burning hours
- IP65-Protection against dust & water with IK08 (Vandal Proof)
- >105 Lumen/Watt (6.5W/700lm)

MRP: ₹ 999/-

HSN Code: 94051090



Endura LED Bulkhead

Wattage available: 9W

Model Number:

WT202W LED6S NW PSU S2 PC

WT202W LED6S CW PSU S2 PC



Specifications & Features

- Surface mounted LED bulkhead to replace 1x60W GLS & 1X11W CFL bulkhead
- Pressure die cast aluminum housing with unbreakable polycarbonate diffuser
- Fit and forget, designed for 50,000 burning hours
- Low power consumption (9W/600lm), available in NW & CW
- IP66 (waterproof) with IK09 impact resistance (Durable)

MRP: ₹ 1,600/-

HSN Code: 94051090

Sleek Surface

Wattage available: 6W, 12W, 15W & 18W

Model Number:

SM250 & SM251 (Circular)

SM260 & SM261 (Square)

Specifications & Features

- Surface/Wall mounted LED downlight for multipurpose utility
- Available in Round and Square with all color temperature CW, NW & WW
- Long life: 30,000 burning hours
- Available in 750lm, 1200lm, 1600lm & 2000lm
- Surge protection of 2.5KV with wide voltage protection range 140V-270V

MRP: 6W: ₹ 1,100/-, 12W: ₹ 1,200/-
15W: ₹ 1,750/-, 18W: ₹ 1,950/-

HSN Code: 94051090



Smartbrite Surface

Wattage available: 32W

Model Number:

SM270C LED 30S 6500 PSU WH

SM270C LED 30S 4000 PSU WH

Specifications & Features

- 32W Surface mounted 4'x1' LED light to replace 2x36W TLD & 2x28W TL5 4'x1' light
- Available in 32W: 2900lm
- Long life: 50,000 burning hours and CRI >80
- Mounting options: surface/ conduit/ suspended
- Available in (NW) 4000K & (CW) 6500K

MRP: ₹ 5,500/-

HSN Code: 94051090



Cirrus Mini Pro

Wattage available: 12W & 20W

Model Number:

SM200C LED16S 6500/4000 PSU OD WH

SM200C LED11S 6500/4000 PSU OD WH

Specifications & Features

- Surface mounted (312mm×312mm×45mm) LED light to replace 2×18W & 2×26W CFL surface mounted downlights
- Available in 12W: 1100lm and 20W: 1600lm
- Surge protection of 3KV with wide voltage protection range 140V-270V
- Long life: 50,000 burning hours
- Available in (NW) 4000K & (CW) 6500K

MRP: 12W: ₹ 2,550/-, 20W: ₹ 3,100/-

HSN Code: 94051090



Coreline 300

Wattage available: 14W & 17W

Model Number:

RC375B LED15S/865 PSU W30L30 PCV IN

RC375B LED15S/840 PSU W30L30 PCV IN

RC375B LED12S/865 PSU W30L30 PCV IN

RC375B LED12S/840 PSU W30L30 PCV IN

Specifications & Features

- Recessed mounted (300mm x 300mm) LED light to replace 2x18W & 2x26W CFL recessed light
- Available in 14W: 1200lm and 17W: 1500lm
- Long life: 25,000 burning hours
- Edge lit LED panel with two color temperature of (NW) 4000K & (CW) 6500K

MRP: 14W: 1,850/-, 17W: 1,950/-

HSN Code: 94051090



Greensquare

Wattage available: 30W

Model Number:

RC140B P LED30S-6500 L60W60 PSU

WH OD

RC140B P LED30S-4000 L60W60 PSU

WH OD

Specifications & Features

- New Elegant recessed LED Luminaire (595mm x 595mm) with uniform light distribution, perfect replacement of 4x14W & 2x36W CFL conventional Light
- System lumen efficacy of 100 lumen/Watt (30W/3000lm)
- Long life: 25,000 burning hours
- Available in (NW) 4000K & (CW) 6500K

MRP: ₹ 3,600/-

HSN Code: 94051090





Coreline Panel

Wattage available: 33W & 40W

Model Number:

RC375B LED30S/865 PSU W60L60 S2 WH

RC375B LED30S/840 PSU W60L60 S2 WH

RC375B LED36S/865 PSU W60L60 S2 WH

RC375B LED36S/840 PSU W60L60 S2 WH

Specifications & Features

- 33W & 40W fully diffused recessed mounted LED luminaire (595mm × 595mm) to replace 4×14W or 2×36W CFL conventional light
- Extruded aluminum housing, 8.2mm depth only
- Edge lit LED panel with light output of 3000lm & 3600lm
- Long life: 25,000 burning hours and easy to install
- Available in (NW) 4000K & (CW) 6500K

MRP: 33W: ₹ 3,800/-, 40W: ₹ 4,200/-

HSN Code: 94051090

Troffer

Wattage available: 24W

Model Number:

RC370B LED30S-6500 G4 L60W60

PSU OD

RC370B LED30S-4000 G4 L60W60

PSU OD

Specifications & Features

- 24W fully diffused recessed mounted LED luminaire (595mm×595mm) to replace 4×14W or 2×36W CFL conventional light
- Backlit LED luminaire with uniform light distribution & light output of 3000lm
- Higher life class: 25,000 burning hour
- Available in (NW) 4000K & (CW) 6500K

MRP: ₹ 4,000/-

HSN Code: 94051090



Coreline Panel

Wattage available: 33W

Model Number:

RC375B LED30S/865 PSU W30L120 S2 WH

RC375B LED30S/840 PSU W30L120 S2 WH

Specifications & Features

- 33W fully diffused recessed mounted LED luminaire (297mm x 1197mm) to replace 2x28W or 2x36W T8 conventional light
- Extruded aluminum housing, 8.2mm depth only
- Edge lit LED panel with light output of 3000lm
- Long life: 25,000 burning hours and easy to install
- Available in (NW) 4000K & (CW) 6500K

MRP: ₹ 4,200/-

HSN Code: 94051090



OUTDOOR



Smart Bright Street

Wattage available: 15W

Model:

BRP040 LED 15 CW RI S1 PSU GR

Specifications & Features

- 15W LED street light to replace conventional street lights upto 40W FTL/CFL
- Efficacy: 100 lumen/watt
- IP65 with 4KV inbuilt surge protection
- Finless design with better street lighting optics
- PDC housing with IK07 protection

MRP: ₹ 1,850/-

HSN Code: 94054090



Greenline Smart

Wattage available: 25W

Model:

BRP020 LED HP/CW 240V 25

Specifications & Features

- 25W LED street light to replace conventional street lights upto 70W
- >90 lumen/watt system efficacy
- IP65 with 4KV inbuilt surge protection
- Sleek design with better street lighting optics
- PDC housing

MRP: ₹ 3,000/-

HSN Code: 94054090





Smart Bright Street

Wattage available: 35W

Model:

BRP050 LED 036 CWR1 MFPC S1 PSU GR

Specifications & Features

- 35W LED street light to replace conventional street lights upto 70W
- Efficacy: 100 lumen/watt
- IP65 with 4KV inbuilt surge protection
- Finless design with better street lighting optics
- PDC Housing

MRP: ₹ 4,400/-

HSN Code: 94054090

Smart Bright Street

Wattage available: 50W, 60W

Model:

BRP060 LED 58 CWRM S1 PSU

BRP060 LED 64 CWRM S1 PSU

Specifications & Features

- 50W -60W LED street light to replace conventional street lights upto 150W
- Efficacy: 110 lumen/watt
- IP65 with 4KV inbuilt surge protection
- Finless design with better street lighting optics
- PDC Housing

MRP: 50W: ₹ 5,000/-, **60W:** ₹ 6,000/-

HSN Code: 94054090



Greenline

Wattage available: 70W

Model:

BRP408 LED HP/CW 240V PSU GR 70W

Specifications & Features

- >90 lumen/watt system efficacy
- CCT: 5700K; full IP65
- Wattage range: 70W
- THD <10%, Surge: 4KV
- Direct substitute up to 100W conventional lamp

MRP: ₹ 7,000/-

HSN Code: 94054090



Essential SmartBright Floodlight

Wattage available: 10W & 20W

Model Number:

BVP131(10W) & BVP132(20W)

Specifications & Features

- Up to 85% energy saving compared with Philips Halogen lamps flood light
- Die cast Aluminum Housing; CRI:80
- Anti Glare: High quality honeycomb pattern light diffuser
- Robust Driver, Wide operating voltage 100V-240V
- Easy to install and maintain, CCT: 3000K, 4000K & 6500K
- 80 lumen/watt system efficacy

MRP: 10W: ₹ 900/-, **20W:** ₹ 1,200/-

HSN Code: 94054090





Smart Bright Flood

Wattage available: 30W, 50W

Model:

BVP 161 LED 26 NW/CW/WW 30W

BVP 161 LED 43 NW/CW/WW 50W

Specifications & Features

- PDC housing with IP65 flood light optics
- Efficient high output LED for direct replacement of conventional flood lights upto 150W
- Available in Warm White, Neutral White & Cool White
- Efficacy: >80 lumen/watt
- Sleek and robust design for better aesthetics

MRP: 30W: ₹ 2,650/-, 50W: ₹ 5,000/-

HSN Code: 94054090



Tempo Mini LED Floodlight

Wattage available: 70W, 100W

BVP182 LED70 CW/NW/WW

BVP182 LED100 CW/NW/WW

Specifications & Features

- PDC housing with IP65 flood light optics
- Efficient high output LED for direct replacement of conventional flood upto 250W
- Available in warm white (WW), Neutral white (NW), Cool White (CW)
- Efficacy: >90 Lumen/watt
- Sleek and robust design for better Aesthetics
- Potted driver
- Toughened and shatter-proof quality built-in lens enhances safety

MRP: 70W: ₹ 7,000/-, 100W: ₹ 9,500/-

HSN Code: 94054090





